

Certificate of Compliance

Certificate: 1246942
Project: 1412500
Issued to: **HOLLISLAND CO., LTD.**
12/F Flat A, One Lok Inn, Hong
Kong
14, Hong To Rd., Kowloon
Kowloon
HONG KONG
Attention: Mr. William Wong, President

Master Contract: 161470 (I.B. 100170)

Date Issued: May 8, 2002

*The products listed below are eligible to bear the CSA Mark shown
with adjacent indicator ▲*



Issued by:

[Signature]
K. J. Jorgensen

Authorized by:

[Signature]
Operations Manager

PRODUCTS

CLASS 142230 - SUPPLEMENTAL FUSES - Component Acceptance

Supplemental, glass cartridge fuses, non-renewable

- Cat. No. 51MS or 51MS0P, pigtail lead, rated 100mA/0.5A, 250V ac and less, R115-100A, R250*, rated 0.1 to 10A, 250V ac or less, R125-100A, R250-100, 5.7 by 20mm.
- Cat. No. 61MS or 61MS0P, pigtail lead, rated 100mA/0.5A, 250V ac and less, R125-100A, R250*, 6.20 by 20mm.
- Cat. No. 51MS, rated 0.1 to 10A, 250V ac or less, R125-100A, R250-100A, 5.7 by 20mm.

Note: Types with R250 have interrupting ratings of 75A for 1A or less, 100A for more than 1A to 5.5A, 500A for more than 5.5A to 10.0A, as applicable for the ampere ratings listed.

APPLICABLE REQUIREMENTS

- CSA Std. C22.2 No. 548.1 - Low-Voltage Fuses - Part 1: General Requirements.
- CSA Std. C22.2 No. 548.14 - Low-Voltage Fuses, Part 14: Supplemental Fuses.
- T.L.L. CA-07 - Component Acceptance Requirements for Supplemental Fuses.